### The 'Element' in profile

#### Powerful motors

The range has increased motor power for greater efficiency

#### High performance gears

Increased wear resistance on the gears for prolonged life and durability

#### Drill chuck adaption

Removable arbor and bearing bracket to add the drill chuck

#### Quick release capstan

Simply push to release for quick dual side operation



# ELEMENT.





#### Lightweight

Inventive designs and advanced manufacturing have ensured the new 'Element' range of magnetic drills are among the lightest available in the world.



#### Performance

High quality components are used throughout the entire manufacturing process ensuring a robust and long lasting product. Accredited to ISO 9001 these products are built in our state of the art factories using cutting edge technology.



#### Design

A team of creative and forward thinking designers take the sleek and modern design of the 'Element' range to the forefront of the industry. Attention to detail delivers a user friendly product whilst at the same time introducing advanced eatures.



#### Operational ease

Cutsmart2<sup>™</sup> takes the difficulty out of drilling a hole. Clever electronics will guide you throughout the cut, optimising the machines performance. This unique feature will protect the machine, enhancing its life span and also maximising the number of holes you can get from the cutter.

#### Rotabroach

## ELEMENT 30 ELEMENT 40



Element 30 Specifications	
Model Number	ELEMENT30/1 // ELEMENT30/3
Motor Specification	110V full load 8 amps 850W // 230V full load 5 amps 850W
No Load RPM	600 RPM
Max hole cutting capacity	Ø30mm x 35mm
Overall dimensions	Height: 406mm // Width: 170mm (with Capstan) // Length: 265 (with guard)
Machine weight	10kgs
Magnetic adhesion	850kgs
Safety features	Cutsmart2™ Technology //Fixed guard // Internal cable // Flush switches

#### Rotabroach



Element 40 Specifications	
Model Number	ELEMENT40/1 // ELEMENT40/3
Motor Specification	110V full load 12 amps 1200W // 230V full load 6 amps 1200W
No Load RPM	Gear One: 600 RPM // Gear Two: 300 RPM
Max hole cutting capacity	Ø40mm x 50mm
Overall dimensions	Height: 510mm // Width: 170mm (with Capstan) // Length: 265 (with guard)
Machine weight	12.2kgs
Magnetic adhesion	850kgs
Safety features	Cutsmart2™ Technology //Fixed guard // Internal cable // Flush switches